

## DATA SHEET

### KM04 EXTENDED TYPE 'K' GENERAL PURPOSE PROBE

#### GENERAL PURPOSE PROBE - 3.0 mm Type 'K'

##### Description

This probe uses the straight handle for fine control. The probe is truly general purpose and may be used for gas, liquid or applications with difficult access.

##### Construction

Minerally Insulated Probe 3.0 mm Diameter by 300mm Long : Stainless Steel 316 (Food Grade) 2M curly polyurethane cable with moulded connector. Complete waterproof assembly.

##### Sensor Features

###### ➤ TOTAL ENCAPSULATION TECHNIQUE FOR MAXIMUM STRENGTH AND DURABILITY.

This results in a solid handle as opposed to a hollow handle. This is particularly important as there is often damage to the handles caused by excess heat. With a hollow handle it is possible to puncture the outer plastic and damage the sensor irreparably.

###### ➤ WATERPROOF HANDLE

Due to the total encapsulation method used, all TME probe handles are completely waterproof.

###### ➤ TOUGH POLYURETHANE CABLE

- Polyurethane cables are used in place of the standard polyurethane for the following reasons :-
- Greater retractability
- Enhanced memory of it's curl
- Non-Toxic
- Greater mechanical strength for durability
- 12 X 0.2mm wires used internally for greater strength.
- PTFE inner insulation for strength and retractability.

###### ➤ HIGH ACCURACY THERMOCOUPLE MATERIAL THROUGHOUT

Type 'K' Thermocouple : Class I ( $\pm 0.5^\circ\text{C} \pm 0.25\%$ )

###### ➤ POLYPROPYLENE HANDLES

Polypropylene is an extremely tough and durable material, commonly used for milk crates, it has good low temperature performance and a relatively high melt temperature. It performs exceptionally well under chemical attack.

###### ➤ WIDE AMBIENT TEMPERATURE SPECIFICATION : -30 TO 50 °C

###### ➤ TIME RESPONSE (96% of value in water) : 2.0 Secs

###### ➤ MEASUREMENT RANGE : -200 TO 1100 °C

##### Cross-reference for compatible instruments

Suitable instruments for use with this probe

TME PART No	DESCRIPTION	APPLICATION
MM2000	SINGLE INPUT INSTRUMENT	HIGH ACCURACY TEMPERATURE MEASUREMENT
MM2010	MAX / MIN HOLD INSTRUMENT	HIGH ACCURACY INSTRUMENT WITH MAX, MIN AND HOLD FEATURES
MM2020	DIFFERENTIAL INSTRUMENT	DUAL INPUT INSTRUMENT FOR DIFFERENTIAL MEASUREMENTS
MM2030	THERMOCOUPLE SIMULATOR	HIGH ACCURACY SIMULATOR WITH MEASUREMENT FACILITY